



A fully self contained LED Floodlight, for outside locations providing 3 hours of emergency lighting. With enclosed control gear and battery pack for simple installation.

- Die Cast Aluminum Housing \checkmark
- **Toughened Glass** \checkmark
- Can connect to PIR \checkmark
- Self-contained \checkmark
- Colour Temp 6000K \checkmark
- Mains Lumens 5892 (50W) \checkmark
- Emergency Lumens 392 (3W) \checkmark

X-FLDLP Options

/50/M	50W - 3 Hour Maintained / Non-maintained
/50/230	50W - 230V AC Mains only

X-FLDLP/	50W
Input Voltage	220-240V
Total Wattage	50W
Function	Maintained / Non-maintained
Lumens Per/Watt	130lm/W
CCT / CRI	6000K / >80
Emergency Duration	3 Hours
Emergency Lumens	392lm
Battery	LiFePO4 3.2V 4.5Ah
Material / Finish	Glass/Diecast / Black
Class / IP	Class 1 / IP66
Beam Angle	120°



Self Contained Floodlight

X-FLDLP

Ringtail



* Limited warranty, enquire for full details Ringtail Lighting maintains a policy of continuous development and reserves the right to change the details shown on this data sheet without notice. The contents are intended for guidance only

www.ringtail.co.uk

FM 582596